

## Data sheet Clic-37

Highly durable and rollable matting system, closed construction.  
Consisting of singularly replaceable aluminium profiles, combined with  
PVC-connecting elements, for integration in a level floor depression  
(mat well).

Including impact sound insulation

Profile height of 18 mm with an overall height of 22 mm.

Distance of profiles 5 mm.

**(Clic-374** Distance of profiles: under 4 mm, fulfills DIN 18650-1 for  
revolving doors)

Weight 19 kg/m<sup>2</sup>.

Fully recyclable

Profile material: Aluminium, ENAW 6063, nature

Fitting 1: needle-punch strips

Fitting material: 100% PP with rubber backing

Fitting color: anthracite, light grey, light blue, light green,  
dark blue, red, gold, beige-brown  
(also available with fire classification **Cfl-s1**  
according to EN 135011:2002-02

Colours: anthracite, light grey and beige-brown)

Slip resistance: R11 according to DIN 51130

Fitting 2: bristle-fused-strips A

Fitting material: 100 % Polypropylen

Fitting color: black or grey

Slip resistance: R12 according to DIN 51130

Load Limit: **110 kN** per 100cm<sup>2</sup> / edge length 10 x 10 cm  
**= 11,200 kg** pressure test, static distributed load  
acc. Test report 2016-9002

Upon level integration in a mat well suitable for traffic such as trucks,  
cars, fork lifts, jack lifts, shopping trolleys, wheelchairs...

Suitable for: shopping centers, airports, entrances with extreme  
Frequenting (approx. 10,000 inspections per day)

**C-Tec GmbH & Co. KG**  
Salzuflener Str. 142  
32602 Vlotho

Fon: +49 5733 88110-0  
Fax: +49 5733 88110-40  
eMail: [info@c-tec-em.de](mailto:info@c-tec-em.de)  
Internet: [www.c-tec-em.de](http://www.c-tec-em.de)

