

Data sheet Clic-38

Highly durable and rollable matting system, closed construction.
Consisting of singularly replaceable aluminium profiles, combined with
PVC-connecting elements, for integration in a level floor depression
(mat well).

Including impact sound insulation

Profile height of 18 mm with an overall height of 22 mm.

Distance of profiles 5 mm.

(Clic-384 Distance of profiles: under 4 mm, fulfills DIN 18650-1 for
revolving doors)

Weight 19 kg/m².

Fully recyclable

Profile material: Aluminium, ENAW 6063, nature

Fitting 1: rubber strips

Fitting material: EPDM 70621

Fitting color: black or grey

Slip resistance: R10 according to DIN 51130

Fitting 2: bristle-fused-strips A

Fitting material: 100 % Polypropylen

Fitting color: black or grey

Slip resistance: R12 according to DIN 51130

Load Limit: **110 kN** per 100cm² / edge length 10 x 10 cm
= 11,200 kg pressure test, static distributed load
acc. Test report 2016-9002

Upon level integration in a mat well suitable for traffic such as trucks,
cars, fork lifts, jack lifts, shopping trolleys, wheelchairs...

Suitable for: shopping centers, airports, entrances with extreme
Frequenting (approx. 10,000 inspections per day)

C-Tec GmbH & Co. KG
Salzuflener Str. 142
32602 Vlotho

Fon: +49 5733 88110-0
Fax: +49 5733 88110-40
eMail: info@c-tec-em.de
Internet: www.c-tec-em.de

