

## Data sheet Clic-48

Highly durable and rollable matting system, open construction.  
Consisting of singularly replaceable aluminium profiles, combined with  
PVC-connecting elements, for integration in a level floor depression  
(mat well).

Including impact sound insulation

Profile height of 18 mm with an overall height of 22 mm.

Distance of profiles 5 mm.

**(Clic-484** Distance of profiles: under 4 mm, fulfills DIN 18650-1 for  
revolving doors)

Weight 17 kg/m<sup>2</sup>.

Fully recyclable

Profile material: Aluminium, ENAW 6063, nature

Fitting 1: rubber strips

Fitting material: EPDM 70621

Fitting color: black or grey

Slip resistance: R10 according to DIN 51130

Fitting 2: bristle-fused-strips A

Fitting material: 100 % Polypropylen

Fitting color: black or grey

Slip resistance: R12 according to DIN 51130

Upon level integration in a mat well suitable for traffic such as shopping  
trolleys, wheelchairs...

Suitable for: 2,000 inspections per day

**C-Tec GmbH & Co. KG**  
Salzuflener Str. 142  
32602 Vlotho

Fon: +49 5733 88110-0  
Fax: +49 5733 88110-40  
eMail: [info@c-tec-em.de](mailto:info@c-tec-em.de)  
Internet: [www.c-tec-em.de](http://www.c-tec-em.de)

