

Data sheet Tec10-37

Highly durable and rollable matting system, closed construction, consisting of singularly replaceable aluminium profiles, with integrated hinges, for integration in a level floor depression (mat well).

Including impact sound insulation

Profile height of 8 mm with an overall height of 10 mm.

Distance of profiles 0 mm fulfills DIN 18650-1 for revolving doors

Weight 9 kg/m².

Fully recyclable

Profile material: Aluminium, ENAW 6063, nature

Fitting 1: needle-punch strips

Fitting material: 100% PP with rubber backing

Fitting color: anthracite, light grey, light blue, light green, dark blue, red, gold, beige-brown
(also available with fire classification **Cfl-s1** according to EN 135011:2002-02

Colours: anthracite, light grey and beige-brown)

Slip resistance: R11 according to DIN 51130

Fitting 2: bristle-fused-strips A

Fitting material: 100 % Polypropylen

Fitting color: black or grey

Slip resistance: R12 according to DIN 51130

Load Limit: **110 kN** per 100cm² / edge length 10 x 10 cm
= 11,200 kg pressure test, static distributed load
acc. Test report 2016-9002

Upon level integration in a mat well suitable for traffic such as cars, fork lifts, jack lifts, shopping trolleys, wheelchairs...

Suitable for: entrances with extreme Frequenting (approx. 10,000 inspections per day)

C-Tec GmbH & Co. KG
Salzuflener Str. 142
32602 Vlotho

Fon: +49 5733 88110-0
Fax: +49 5733 88110-40
eMail: info@c-tec-em.de
Internet: www.c-tec-em.de

