

Waterhog Plus™ Specifications

General Specifications

Surface	Type:	Solution Dyed P.E.T.
	Weight:	800 gr/m ²
	Rubber Nub Height:	0,64 cm
	Pattern:	Swirl Pattern
Backing	Type:	100% Nitrile Rubber
	Border Thickness:	4,5 mm
	Rubber Nubs	2,3 mm
Total Weight	4 kg/m ²	

Features

- Reinforced face NUBS: Face Nubs are reinforced with rubber to resist crushing, maintaining high performance and extending product life.
- "Water Dam" border: Border is designed to hold water and dirt on mat keeping them off carpets and floors. Unique raised rubber border allows WaterHog Plus mats to hold up to 4 liters of water per square meter.
- Raised NUB surface: Removes and traps dirt and moisture, holding it on the mat below shoe level so they are not tracked onto floors.
- Rubber backing: 100% Nitrile rubber lays flat, and will not crack or curl like vinyl mats.
- Indoor/Outdoor: Durable anti-static P.E.T. face suitable for indoor or outdoor use. P.E.T. fiber system dries quickly.
- Colorfast: Solution dyed for excellent light fastness.
- Not adversely affected by salt or ice melt
- Passes Flammability Standard DOC-FF-1-70.
- Anti-Static: WaterHog Plus mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99).
- ASTM C 1028-89 Static Coefficient of Friction Dry .70